

# Material Safety Data Sheet

Product Name Indo Machine Oil

#### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name TRU-BLU OIL AUSTRALIA PTY LTD

Address 6 Dunlop Court, Bayswater, Victoria, AUSTRALIA, 3153

 Telephone
 (03) 9720 4400

 Fax
 (03) 9720 5821

 Emergency
 0412 609 722

Email technical@trubluoil.com.au

Web Site http://www.trubluoil.com.au/

Synonym(s) INDO 100, INDO 150, INDO 22, INDO 220, INDO 32, INDO 320, INDO 46, INDO 460, INDO

68

Use(s) Machine Oil

**SDS Date** 2<sup>nd</sup> December 2015

## 2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Risk Phrase(s) N/a

Safety Phrase(s) N/a

#### 3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
Paraffin Oil – Highly Solvent Refined	Not Available	64742-65-0	<85%
Petroleum Residual Oils – Solvent Dewaxed	Not Available	64742-62-7	1-15%
Additive(s)	Not Available	Not Available	<10%

#### 4. FIRST AID MEASURES

Eye If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing

until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

**Skin** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with

running water. Continue flushing with water until advised to stop by a Poisons Information

Centre or a doctor.

**Inhalation** If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

Ingestion For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at

once). If swallowed, do not induce vomiting.

Advice to Doctor Treat symptomatically.

**Indo Machine Oils** 

First Aid Facilities Eye wash facilities and safety shower should be available.

#### 5. FIRE FIGHTING MEASURES

**Flammability** Combustible. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to

decomposition.

Fire and Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation.

Remain upwind and notify those downwind of hazard. Wear full protective equipment

including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

Extinguishing Dry agent, carbon dioxide or foam. Prevent contamination of drains or waterways.

**Hazchem Code** None Allocates

**Explosion** 

#### 6. ACCIDENTAL RELEASE MEASURES

**Spillage** Use personal protective equipment. Clear area of all unprotected personnel. Ventilate area

> where possible. Contain spillage, then cover/absorb with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

## 7. STORAGE AND HANDLING

Storage Store in a cool, dry, well-ventilated area, removed from oxidising agents, acids, alkalis, heat or

ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate fire protection systems. Store as a Class C2 Combustible Liquid (AS1940)

Handling

Before use, carefully read product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before

eating. Prohibit eating, drinking and smoking in contaminated areas.

# 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

#### **Exposure Standards**

Ingredient	Reference	TWA		STEL	
Mineral Oil Mist	SWA (AUS)		5 mg/m3		

**Biological Limits** No biological limit allocated.

**Engineering Controls** Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists,

mechanical extraction ventilation is recommended. Maintain vapour levels below

the recommended exposure standard.

PPE Wear splash-proof goggles and rubber or PVC gloves. When using large quantities or

where heavy contamination is likely, wear: coveralls. Where an inhalation risk exists, wear: a Type A (Organic vapour) respirator. With prolonged use, wear: Viton (R) or

nitrile gloves and coveralls.



Reviewed Date: 02/12/2015

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** Yellow Liquid

Odour 0.865 - 0.900Characteristic Odour **Specific Gravity** рH Not Relevant % Volatiles Not Available

**Vapour Pressure** Not Available **Flammability** Class C2 Combustible

**Vapour Density** Not Available **Flash Point** >200°C **Boiling Point** Not Available **Upper Explosion Limit** Not Available **Melting Point** Not Available **Lower Explosion Limit** Not Available Viscosity 32 to 460 cSt @100°C Solubility (Water) Insoluble

## 10. STABILITY AND REACTIVITY

**Chemical Stability** Stable under recommended conditions of storage.

**Conditions to Avoid** Avoid heat, sparks, open flames and other ignition sources.

**Materials to Avoid** Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis

(e.g. hydroxides), heat and ignition sources

Hazardous

May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

Decomposition **Products** 

Hazardous Reactions Polymerization is not expected to occur.

#### 11. TOXICOLOGICAL INFORMATION

**Health Hazard** Low toxicity. Use safe work practices to avoid eye or skin contact and inhalation. The mineral

oil contained within this product is highly refined and therefore is not classifiable as to its

carcinogenicity in humans (IARC Group 3).

Low to moderate irritant. Contact may result in irritation, lacrimation, pain and redness. Eye

Inhalation Low irritant. Over exposure may result in irritation of the nose and throat, with coughing

Skin Low irritant. Prolonged or repeated contact may result in mild irritation, rash and dermatitis.

Ingestion Low toxicity. Ingestion of large quantities may result in nausea, vomiting, abdominal pain,

diarrhoea, and drowsiness. Aspiration may result in chemical pneumonitis and pulmonary

oedema

**Toxicity Data** No LD50 data available for this product.

## 12. ECOLOGICAL INFORMATION

**Environment** Mineral oils biodegrade slowly and should not be released to waterways or soil. They can

float on water, restricting oxygen exchange with possible asphyxiation of aquatic life.

**Ecotoxicity** Not classified as dangerous to the aquatic environment.

Persistence/ Degradability

Expected to be inherently biodegradable

Mobility Low solubility and is expected to migrate from water to the land. Expected to partition to

sediment and wastewater solids.

**Indo Machine Oils** 

Reviewed Date: 02/12/2015

## 13. DISPOSAL CONSIDERATIONS

Waste Disposal Reuse where possible or return to the manufacturer. May be recycled. Do not release to

drains or waterways. Contact the manufacturer for additional information

**Legislation** Dispose of in accordance with relevant local legislation.

#### 14. TRANSPORT INFORMATION

#### NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping None Allocated Packing Group None Allocated Hazchem Code None Allocated

Name

UN No. None Allocated DG Class None Allocated Subsidiary None Allocated

Risks(s)

# 15. REGULATORY INFORMATION

Poison Schedule A poison schedule number has not been allocated to this product using the criteria in the

Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

#### **16. OTHER INFORMATION**

#### **Additional Information**

MINERAL OILS - SOLVENT REFINED; Animal experiments and human experience have not shown cancer risks when handling solvent refined mineral oils, unlike non refined mineral oils. CLEANING MINERAL OIL CONTAMINATED CLOTHING; Cleaners are advised that when cleaning oil contaminated clothing it is essential that freshly distilled solvent is used for each batch, including final rinse, as even filtered solvent will leave oil residues.

MINERAL OILS - USED; Used mineral oils in engine crankcases and other high temperature/high stress environments may contain potentially harmful residues, some of which have been shown to cause irreversible skin effects, including cancer. Prolonged and repeated inhalation of mists associated with used mineral oils may result in pulmonary fibrosis.

MINERAL OILS - INJECTION; Where high pressure applications are used the risk of accidental injection under the skin exists and may result in an extremely painful and serious injury requiring immediate medical attention. Depending on the pressure used, mineral oils may be injected a considerable distance below the skin and may cause permanent tissue damage. SEEK IMMEDIATE MEDICAL ATTENTION. EXERCISE EXTREME CARE WHEN USING HIGH PRESSURE EQUIPMENT.

ABBREVIATIONS: ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EC No - European Community Number.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m3 - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

TWA/ES - Time Weighted Average or Exposure Standard.

**HEALTH EFFECTS FROM EXPOSURE:** 

**Indo Machine Oils** 

Reviewed Date: 02/12/2015

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a MSDS which would encompass all possible scenarios, it is anticipated that the end user will assess the risks and apply control methods where appropriate.

#### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this MSDS is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered by the end user before final selection of personal protective equipment is made.

#### **REPORT STATUS:**

This MSDS has been prepared by Tru-Blu Oil using the most current information available at the time of issuing. Tru-Blu Oil accepts no liability (as lawfully allowed) for any loss, injury or damage which may have been suffered or incurred by any person as a consequence of their reliance on information that is contained in this MSDS.

MSDS Date: 2<sup>nd</sup> December 2015

**End of MSDS**