Product Name: Duro Hydraulic Oil ISO 46

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name TRU-BLU OIL AUSTRALIA PTY LTD

Address 6 Dunlop Court , Bayswater , Victoria, AUSTRALIA, 3153

 Telephone
 (03) 9720 4400

 Fax
 (03) 9720 5821

 Emergency
 0412 609 722

Emailtechnical@trubluoil.com.auWeb Sitehttp://www.trubluoil.com.au/

Synonym(s) Duro Ultra Hydraulic Oil 46, Duro Ultra 46, Duro EL 46

Use(s) Hydraulic Oil.

SDS Date 8th August 2022

2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA NOT CLASSIFIED AS A HAZARDOUS GOOD BY THE CRITERIA OF THE GHS CLASSIFICATION.

SIGNAL WORD: Not Applicable

PICTOGRAMS: Not Applicable

HAZARD STATEMENTS: Not Applicable

PRECATIONARY STATEMENTS:

PREVENTION: Not Applicable

RESPONSE: Not Applicable

STORAGE: Not Applicable

DISPOSAL: Not Applicable

Dangerous Goods Classification:

Not classified as dangerous goods by the criteria of the "Australian code for transport of dangerous goods by road and rail" and the "New Zealand NZS5433: transport of dangerous goods on land"

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content	GHS
Severly treated base oil, mixture of petroleum lubricating base oils	Not Available	Not Available	>99%	Not Classified
Ingredients determined to be nonhazardous	Not Available	Not Available	<1%	Not Classified

4. FIRST AID MEASURES

Inhalation: If inhaled, remove affected person from contaminated area. If you are providing

assistance avoid exposure to yourself, where appropriate PPE. Apply artificial

respiration if affected person not breathing. Seek medical assistance.

Skin: Wash contact areas with soap and water. Remove contaminated clothing and

launder before reuse. If product is injected into or under the skin or into any body part, regardless of the appearance of the wound or its size the individual should be evaluated immediately by a physician. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment with

the first few hours may significantly reduce the ultimate extent of injury.

Eyes: If in eyes, hold eyelids apart and flush continuously with running water for at least

15 minutes. If irritation occurs, seek medical assistance.

Ingestion: Rinse mouth out with water. If swallowed, do not induce vomiting. If vomiting

occurs lean patient forward or place on left side head down position to maintain open airway and prevent aspiration. For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor and seek medical assistance.

PPE for First Aiders: Wear overalls, chemical goggles and nitrile gloves. Use with adequate ventilation.

If inhalation risk exists wear organic vapour/particulate respirator. Always wash your hands after assisting. Wash contaminated clothing and other PPE after use.

First Aid Facilities: Eye wash facilities and safety shower should be available.

Most Important symptoms and effects caused by exposure:

Acute: Ingestion or inhalation of vapours may lead to irritation of the mouth and

respiratory tract. Ingestion may lead to nausea and diarrhoea. In the eye may lead

to localised burning, redness and tears. Skin contact may lead to redness or

itching.

Chronic: Contact with the skin may aggravate existing skin conditions such as dermatitis.

Advice to Doctor: Treat symptomatically as the product is hydrocarbon based. If vomiting has

occurred after ingestion, the patient needs to be monitored to ensure the

product has not been aspirated into the lungs.

5. FIRE FIGHTING MEASURES

Extinguishing Media: Dry agent, carbon dioxide or foam. You can spray down fumes from fire using a

waterspray. Prevent contamination of drains or waterways.

Unsuitable Media: Do not use water jet directed at fire or residual material that may be burning as

water may/will cause splattering on hot residue as this product will float on

water.

Hazchem Code None Allocated

Advice for Fire Brigade:

Fire: Product is not flammable under normal conditions of use. It is hydrocarbon based

and product will burn if preheated. Keep storage tanks, pipelines and fire exposed

surfaces cool with waterspray.

Explosion: No information of product being explosive. Closed containers of the product may

explode when exposed to extreme heat.

Note: Evacuate area and contact emergency services. Toxic gases may evolve in a fire

situation. Remain upwind and notify those downwind of hazard. Wear full protective clothing and Self Contained Breathing Apparatus (SCBA) when

combating fire. Use water-fog to cool intact containers and nearby storage areas.

6. ACCIDENTAL RELEASE MEASURES

PPE: Personnel must wear gloves, goggles or glasses, boots full length clothing during

the cleaning procedure. If mists and vapours are involved an approved half face organic vapour/particulate respirator is required. Use respirators in accordance

with standards AS 1715 and AS 1716.

Spillage: Use personal protective equipment. Clear area of all unprotected personnel.

Ventilate area where possible. Contain spillage, then cover/absorb with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. In the event of a spill or accidental release notify

the relevant authorities in accordance with all applicable regulations.

Spillage and Environment:

Do not allow product to enter drains, surface water, sewer or watercourses

please inform local authorities if this occurs.

Containment: Contain the spill and absorb with absorbent material, sand or soil. For large spills

prepare a bund/barrier ahead of the spill to contain the spill. If there is the

possibility the spill to enter drains, storm water, sewer or waterways please make sure you bund the areas of concern. Make sure drains are covered to minimise

the potential for this to occur.

Cleaning: After spill contained, collect all spilled material and material used to clean up the

spill in suitable containers. Follow local regulations for the disposal of waste. Personnel must wear gloves, goggles or glasses, boots full length clothing during the cleaning procedure. Wash contaminated area and equipment used to clean up in detergent and water after the spill has been cleaned up. Rinse area with water and don't allow the cleanup water to enter drains or water ways.

7. STORAGE AND HANDLING

Storage: Store in a cool, dry, well ventilated area, removed from oxidising agents, acids,

alkalis, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate fire protection systems. Store as a Class C2 Combustible Liquid (AS1940).

Handling: Before use carefully read the product label. Use of safe work practices are

recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and

smoking in contaminated areas.

Incompatibilities: Oxidising substances including strong acids.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Standards

Ingredient	Reference	T	WA	ST	EL
Mineral oil mist	SWA (AUS)		5 mg/m3	-	mg/m3

Biological Limits No biological limit allocated.

Control Banding: No information available.

Engineering Controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists,

mechanical extraction ventilation is recommended. Maintain vapour levels below

the recommended exposure standard.

Individual Protection Measure:

Eye & Face Protection: Wear goggles/glasses and if there is a risk of splashing wear a full face shield. Use

eye protection in accordance with AS 1336 & AS 1337

Skin Protection: Wear gloves. Nitrile rubber gloves are recommended. Wear long sleeved clothing

to avoid skin contact. Soiled clothing should be washed properly with detergent

prior to re-use

Respiratory Protection:

Not required during routine use. If mists or vapours are generated use an approved half face filter respirator suitable for organic vapours. Use in accordance with AS 1715 & AS 1716

Thermal Protection: Not Applicable

9. PHYSICAL AND CHEMICAL PROPERTIES

A	Clarata Vallandiania	
Appearance:	Clear to Yellow Liquid	
Odour:	Characteristic Odour	
Odour Threshold:	No data available	
pH:	Not applicable	
Melting point/freezing point:	Not applicable	
Initial boiling point:	No data available	
Boiling range celsius:	No data available	
Flash point celsius:	>200	
Evaporation rate:	No data available	
Flammability (solid, gas):	No data available	
Vapour Pressure (mmHg):	No data available	
Vapour Density:	No data available	
Density (g/ml @ 15C):	0.8658	
Solubility in water (g/L):	Insoluble in water	
Partition coefficient: n-octanol/water	No data available	
Auto-ignition Temperature:	No data available	
Decomposition temperature:	No data available	
Viscosity (cSt @ 40 c)	Typically 46	
Viscosity (cSt @ 100 c)	Typically 6.9	

10. STABILITY AND REACTIVITY

Reactivity: This product does not pose any further reactivity hazards other than those listed

below in Section 11.

Chemical Stability Stable under recommended conditions of storage and handling conditions.

Conditions to Avoid Avoid heat, sparks, open flames and other ignition sources.

Materials to Avoid Incompatible with oxidising agents (e.g. hypochlorites), acids

(e.g. nitric acid), alkalis (e.g. hydroxides), heat and ignition sources

Hazardous Decomposition Products

May evolve into toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

Hazardous Reactions Polymerization is not expected to occur.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity: If swallowed this product is expected to have low toxicity. It may cause

irritation to the mouth throat and digestive tract. Use safe work practices

to avoid eye or skin contact and inhalation.

Skin corrosion/irritation: Low irritant. Prolonged or repeated contact may result in mild irritation,

rash and dermatitis. Correct handling procedures incorporating protective

clothing and gloves should minimise the risk of skin irritation.

Serious eye damage/irritation: Low to moderate irritant. Contact may result in irritation, lacrimation,

pain and redness. Symptoms may include localised burning, redness and tears. Correct handling procedures incorporating eye protection should

minimise the risk of eye irritation.

Respiratory or skin sensitisation:

This product is not expected to be a respiratory tract sensitiser based on

known hazards of the products components. This product is not expected to be a skin sensitiser based on known hazards of the products

components.

Germ Cell Mutagenicity: Not expected to be a germ cell mutagen based on the assessment of

components.

Carcinogenicity: Not expected to cause cancer. Based on the assessment of the

components.

Reproductive Toxicity: Not expected to be a reproductive hazard based on available data and the

known hazards of the components.

Specific Target Organ Toxicity (STOT) – Single Exposure:

This product is not expected to cause organ damage from single exposure, based on available data and known hazards of the components. This product is not expected to be an irritation hazard at ambient temperature under normal conditions. Not classified as a respiratory irritant, please note the inhalation of vapours or mist may cause irritation to the nose, throat and respiratory system.

Specific Target Organ Toxicity (STOT) – Repeated Exposure:

This product is not expected to cause organ damage from Prolonged or repeated exposure, based on available data and known hazards of the components.

Aspiration Hazard: This product is not expected to be an aspiration hazard based on available data

and the known hazards of its components. Note as the product is hydrocarbon based if vomiting has occurred after swallowing the person should be monitored

for adverse effects.

Note: Used oils may contain harmful substances that can accumulate during use. All

used oils should be handled with caution and skin contact should be avoided by

wearing gloves made from nitrile rubber.

12. ECOLOGICAL INFORMATION

Ecotoxicity: May be harmful to the aquatic environment. Mineral oils should not be

released to waterways. They can float on water, restricting oxygen

exchange with possible asphyxiation of aquatic life.

Persistence/ Degradability: Not expected to be biodegradable. Note: major parts of the product are

expected to be inherently biodegradable, the product contains parts that

may persist in the environment.

Bioaccumulative Potential: No information is available.

Mobility in soil: If the product enters the soil it is expected that it will absorb onto soil

particles and will not be mobile.

Other Adverse Effects: Based on available data and known hazards of the products components,

this product is not expected to have ozone depletion potential,

photochemical ozone creation potential or global warming potential. The product is a mixture of non-volatile components, which are not expected

to be released into the air in any significant amounts.

13. DISPOSAL CONSIDERATIONS

Disposal Methods:

Product: This product should not be released into the environment, any unused material should be

recycled where possible or disposed of as hazardous waste at an appropriate collection

depot. Dispose of in accordance with relevant government legislation.

Containers: Empty containers may contain residual oil. Containers should be completely drained and

stored safely. Empty containers should be taken for recycling or disposal through suitably

licensed contractors in accordance with government regulations.

Note: Do not pressure, cut, weld, braze, solder, drill, grind or expose such containers to heat,

flame, sparks, static electricity, or other sources of ignition. They may explode and cause

injury or death.

Note: Local council and / or state environment authority may be able to provide advice on the

disposal of this product.

14. TRANSPORT INFORMATION

This product is not regulated for land, sea or air transport.

Land Transport			
Land (ADG Code):	Not Applicable		
UN Number	Not Applicable		
UN Proper Shipping Name:	Not Applicable		
Transport Hazard Class:	Not Applicable		
Packing Group:	Not Applicable		
Environmental Hazards for Transport Purposes:	Not Applicable		
Special Precautions for Users:	Not Applicable		
Additional Information:	Not Applicable		
Hazchem Code:	Not Applicable		
Sea Transport			
SEA (IMDG Code):	Not Applicable		
UN Number	Not Applicable		
UN Proper Shipping Name:	Not Applicable		
Transport Hazard Class:	Not Applicable		
Packing Group:	Not Applicable		
Environmental Hazards for Transport Purposes:	Not Applicable		
Special Precautions for Users:	Not Applicable		
Air Transport			
AIR (IATA Code):	Not Applicable		
UN Number	Not Applicable		
UN Proper Shipping Name:	Not Applicable		
Transport Hazard Class:	Not Applicable		
Packing Group:	Not Applicable		
Environmental Hazards for Transport Purposes:	Not Applicable		
Special Precautions for Users:	Not Applicable		

15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations:

Applicable Regulations:			
SUSMP:	Not Scheduled		
AICS:	All Ingredients are listed in the AICS list		
Montreal Protocol: (Ozone depleting substances)	Not Applicable		
Stockholm Convention: (Persistent Organic Pollutants)	Not Applicable		
Rotterdam Convention: (Prior Informed Consent)	Not Applicable		
Basel Convention: (Hazardous Waste)	Not Applicable		
International Convention for the Prevention of Pollution from Ships (MARPOL)	Annex 1 Oil		
GHS Classification Hazard Class & Category and Hazard Statement:	Not Applicable		
HSNO Approval Number:	Not Applicable		
HSNO Group Title:	Not Applicable		

16. OTHER INFORMATION

The organic materials consist of paraffinic, naphthenic and aromatic oils.

MINERAL OILS - SOLVENT REFINED; Animal experiments and human experience have not shown cancer risks when handling solvent refined mineral oils, unlike non refined mineral oils. CLEANING MINERAL OIL CONTAMINATED CLOTHING; Cleaners are advised that when cleaning oil contaminated clothing it is essential that freshly distilled solvent is used for each batch, including final rinse, as even filtered solvent will leave oil residues.

MINERAL OILS - USED; Used mineral oils in engine crankcases and other high temperature/high stress environments may contain potentially harmful residues, some of which have been shown to cause irreversible skin effects, including cancer. Prolonged and repeated inhalation of mists associated with used mineral oils may result in pulmonary fibrosis.

MINERAL OILS - INJECTION; Where high pressure applications are used the risk of accidental injection under the skin exists and may result in an extremely painful and serious injury requiring immediate medical attention. Depending on the pressure used, mineral oils may be injected a considerable distance below the skin and may cause permanent tissue damage. SEEK IMMEDIATE MEDICAL ATTENTION. EXERCISE EXTREME CARE WHEN USING HIGH PRESSURE EQUIPMENT.

ABBREVIATIONS:

ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EC No - European Community Number.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m3 - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

PPE – Personal Protection Equipment ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

TWA/ES - Time Weighted Average or Exposure Standard.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a SDS which would encompass all possible scenarios, it is anticipated that the end user will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this SDS is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered by the end user before final selection of personal protective equipment is made.

REPORT STATUS:

This SDS has been prepared by Tru-Blu Oil using the most current information available at the time of issuing. Tru-Blu Oil accepts no liability (as lawfully allowed) for any loss, injury or damage which may have been suffered or incurred by any person as a consequence of their reliance on information that is contained in this SDS.

SDS Date: 8th August 2022 End of Report

www.trubluoil.com.au Page 10 Last Edited: 08/08/2022